



Elite Specs - Tile Floor Cover

2018

Construction: Nonwoven (Needle punch)

Texture: Hobnail

UV Stabilized: ASOTA Polypropylene

Face weight: 52 oz/sq yd

Backing: Composite rubber

Total weight: 93 oz/sq yd

Pile height: .400 inch (variable)

Total height: .500 inch (variable)

Tile size: 36 in x 72 in

Flammability: Meets or exceeds U.S. Minimum Requirements COUNTRY OF ORIGIN & The Netherlands

Certification: CRI Green Label Plus. 150 ISO 9002 & 14001 Environmental Certification

PRODUCT DESCRIPTION	
Material	100% solution dyed UV stabilized polypropylene fibers
Backing	Composite rubber
Roll Size	12'x125'
Custom Sizes	Custom lengths up to 125'

TECHNICAL DATA	REQUIREMENTS	DATA
Pile Height	inches	.400 in (variable)
Total Height	inches	.500 in (variable)
Pile Weight	ounce/square yard	52 ounce/square yard
Total Weight	ounce/square yard	93 ounce/square yard

LEED			
MR Credit 4	LEED-NC v.3	For 1-2 points: \$ value of all materials minimum average 10% recycled content	20% post recycled (post-consumer)
IEQ Credit 4.1	LEED-NC v.3	For 1 point: low-emitting adhesive with a VOC of 50 g/L or less for indoor carpet	Multi-Bond VOC: 0 g/L
IEQ Credit 4.3	LEED-NC v.3	For 1 point: low-emitting flooring per Green Label Plus or FloorScore™	Green Label Plus Certified
IEQ Credit 5	LEED-NC v.3	For 1 point: semi-permanently installed entrance system at least ten feet in and maintained on a weekly basis by a length contracted service organization	Elite Pro 52 is designed for semi-permanent installation



For more information or samples, please email info@elitecarpetandmats.com

Elite Carpet & Matting Company

3182 Farmington Drive Atlanta, GA 30339

404-500-MATS (6287)

